

SAF-RC0920-5M | IPRAS-RC-M-23FA0920

- 通过 USB 连接实现镜头聚焦、光圈电动控制 Connection via USB for controlling focus/Iris
- 2/3 英寸 500 像素、250mm 工作距设计 2/3“ 5Mpixel WD250mm
- 配合无序被动聚焦系统（IPRAS），实现一键自动聚焦或 ROI 连续自动聚焦
Supported by IPRAS (Intelligent Passive Random Autofocus System) to autofocus or constantly autofocus under one key or AOI



焦距EFL		9mm				工作 距离WD	倍率 Mag	2/3 “		1/1.8	
靶面Format		2/3” (Ø13)				—	—	—	—	—	—
分辨率Resolution		5MP				—	—	—	—	—	—
接口Mount		C				—	—	—	—	—	—
范围 Range	光 圈 Aperture	F2.0				—	—	—	—	—	—
	聚 焦 Focus	250mm				250	0.034	253.16	211.28	220.38	146.42
控制 Control	光 圈 Iris	电动Motorized				300	0.0286	300.54	250.88	261.68	173.88
	聚 焦 Focus	电动Motorized				350	0.0247	347.94	290.48	302.96	201.36
视场 FOV	对角D	2/3”	63.5	1/1.8”	52.9	400	0.0217	395.32	330.08	344.26	228.84
	水平H		52.5°		44.8°	450	0.0194	442.72	369.68	385.56	256.3
	垂直V		40.5		30.2°	500	0.0175	490.1	409.3	426.86	283.78
畸变Distortion		< 0.3%				550	0.016	537.48	448.9	468.16	311.26
机械后焦MBF		10.398mm				600	0.0146	584.88	488.5	509.46	338.72
滤片尺寸Filter		M40.5x0.75				650	0.0132	640.15	535.61	558.33	372.73
控制接口Interface		USB				700	0.0126	679.66	567.7	592.04	393.68
工作温度Temp.		-20℃ ~ +70℃				800	0.011	774.44	646.9	674.64	448.62
外观尺寸Size		42.3x60mm				900	0.0098	869.22	726.1	757.24	503.56
重量 (含线) Weight		203.5g				1000	0.0089	964	805.32	839.82	558.52
通讯线长度Cable		1500mm									